

## INDUSTRIAL PLUS RANGE

# FAL IPR20G



Normative:	EN-ISO 20345:2011 S3+SRC+CI
Reference:	246643
Sizes:	35 a 48 EU
Height:	6 cm internally ( $\pm 5\%$ ) [Size 42]
Weight:	1.10 Kg/pair (APROX) [Size 42]

## DESCRIPTION

Water-resistant cordura-like textile and split leather shoe with lycra. Vincap non-metallic toe cap. Textile puncture resistant insole. SRC slip resistant bi-density polyurethane sole.

**Upper:** Water resistant cordura like fabric and split leather.

**Lining:** Synthetic fabric: high breathability and abrasion resistance. Foamed.

**Removable Insole:** Anatomic preformed with antibacterial treatment. It allows 30° washing and it is abrasion resistant.

**Sole:** Double density polyurethane with anti-slip design.


**Protection toecap:** Composite (light, non-magnetic, thermally isolated, recovers form after normative impact).

**Protective Insole:** Non-metallic penetration resistant insole (High Tenacity Polyester).


## TECHNICAL INFORMATION




## FEATURES




SPLIT LEATHER



CORDURA-LIKE FABRIC



BREATHABLE LINING



FUEL OIL RESISTANT



NON METALLIC TOECAP



FLEXIBLE ANTI-PUNCTURE  
INSOLE



WASHABLE REMOVABLE  
INSOLES